



transmatic

Heat Seal Machines



TS 100/70P

TS 100/70P

I	Dimensione piastra	100x70 cm
	Tensione alimentazione	380 V
	Potenza max.	KW 4,5
	Consumo	KW/h 2,2
	Temperatura	50°-255° C
	Tempo regolabile	0-760 sec.
	Pressione	400 gr/cm ² 6 Bar
	Peso netto	Kg 310

Pressa pneumatica semi-automatica. Struttura robusta dotata di due cilindri. Regolazione elettronica digitale del tempo e della temperatura con indicatore dei guasti. Copertina Nomex incl.

D	Abmessungen des Plateaus	100x70 cm
	Spannung	350 V
	Anschlusswert	KW 4,5
	Anschlusswert/h	KW/h 2,2
	Temperatur	50°-255° C
	Zeiteinstellung	0-760 Sek.
	Anpressdruck	400 gr/cm ² 6 Bar
	Gewicht netto	Kg 310

Halb-automatische, pneumatische Presse. Extrem robuste Struktur. Digitalinstrumentation mit Sichtkontrolle der Temperatur und der Zeit, Fehlerquellenanzeige. Inkl. Nomexschutzbezug.

UK	Dimension of the plate	100x70 cm
	Current	380 V
	Power consumption	KW 4,5
	Power consumption/h	KW/h 2,2
	Temperature	50°-255° C
	Time regulable	0-760 sec.
	Pressure	400 gr/cm ² 6 Bar
	Net weight	Kg 310

Half-automatic pneumatic press. Strong construction. Electronic and digital instruments with visual control of time, temperature, and advise of eventual errors. Nomex-cover included.

F	Dimension de la plaque	100x70 cm
	Voltage	380 V
	Consommation totale	KW 4,5
	Consommation totale/h	KW/h 2,2
	Température	50°-255° C
	Régulations du temps	0-760 sec.
	Pression	400 gr/cm ² 6 Bar
	Poids net	Kg 310

Presse à chaud semi-automatique pneumatique. Structure robuste. Instrumentation électronique digital du temps est de la température avec indicateur de dommage, toil nomex incl.



I dati e le caratteristiche tecniche sono puramente indicativi e soggetti a variazioni senza obbligo di preavviso.

All data and technical features are purely indicative and subject to changes without prior notice.



transmatic s.r.l.

Via Enzo Ferrari, 9/11/13
20824 Lazzate (MB) - ITALY
Tel. +39 02 96329816 - +39 02 96329024
Fax: +39 02 96728422
e-mail: info@transmaticsril.com
web: www.transmaticsril.com