

POSTBED-TOP & BOTTOM ROLLER FEED

SPECIFICATIONS:

Model No.	 Max. Sewing Speed S.P.M.	 Lifting Of Roller Presser (Knee) mm	 Max. Stitch Length mm	 Needle Bar Stroke mm	Hook System	Needle System	Postbed	Height Of Postbed mm
CS-8369	2500	15	7	38	Standard Hook	DP×5 #16 (#14~#19)	Left-Side	175
CS-8369S	2500	15	7	38	Small Hook		Left-Side	175
CS-8369M	2500	15	7	38	Standard Hook	DP×5 #16 (#14~#19)	Left-Side	220
CS-8369MS	2500	15	7	38	Small Hook		Left-Side	220
CS-8369MH	2500	15	7	38	Standard Hook	DP×5 #16 (#14~#19)	Left-Side	315
CS-8369MHS	2500	15	7	38	Small Hook		Left-Side	315
CS-8369MHSN	2500	15	7	38	Small Hook	DP×5 #16 (#14~#19)	Left-Side	315
CS-8369HS	2500	15	7	38	Small Hook		Left-Side	420
CS-8369R	2500	15	7	38	Standard Hook	DP×5 #16 (#14~#19)	Right-Side	175
CS-8369SR	2500	15	7	38	Small Hook		Right-Side	175
CS-8369MR	2500	15	7	38	Standard Hook	DP×5 #16 (#14~#19)	Right-Side	220
CS-8369MSR	2500	15	7	38	Small Hook		Right-Side	220
CS-8369MHR	2500	15	7	38	Standard Hook	DP×5 #16 (#14~#19)	Right-Side	315
CS-8369MHSR	2500	15	7	38	Small Hook		Right-Side	315
CS-8369D-R	2500	15	7	38	Standard Hook	DP×5 #16 (#14~#19)	Right-Side	175
CS-8369D-RT	2500	15	7	38	Standard Hook		Right-Side	175
CS-8369-2	2500	15	4	41	Standard Hook	DP×5 #16 (#14~#19)	Double Needle	175
CS-8369S-2	2500	15	4	41	Small Hook		Double Needle	175
CS-8369MH-2	2500	15	4	41	Standard Hook	DP×5 #16 (#14~#19)	Double Needle	315
CS-8369MHS-2	2500	15	4	41	Small Hook		Double Needle	315

CS-8369-2



Double Needle, Top/Bottom Roller Feed, Slender Postbed Sewing Machine. (Low postbed, standard hook)

CS-8369D-RT



Direct Drive, Single Needle, Needle Feed & Top/Bottom Roller Feed, Slender Postbed Sewing Machine. (With direct drive servo motor, right-side & low postbed, standard hook, automatic undertrimming).

With direct drive servo motor & automatic undertrimming, ensured high sewing efficiency & electricity saving.



CS-8369

Single Needle, Needle Feed & Top/Bottom Roller Feed, Slender Postbed Sewing Machine. (Left-side & low postbed, standard hook)



Model No. CS-8369	S.P.M. 2,500
Max.Stitch Length 7mm	Lift Of Roller Presser (Knee) 15mm
Needle System DP×5 #16 (#14~#19)	Needle Bar Stroke 38mm
Height Of Postbed 175mm	

BOBBIN CASE OPENER & FEEDING MECHANISM(PATENT): Special designed bobbin case opener, the hook cover is close to the rotating hook, and the distance between the needle and the side of postbed is very tiny. It is suitable for stitching the three-dimensional or small-curved articles. Special designed feeding mechanism and in vertical order, could narrow the distance between the needle and the side of postbed. It is suitable for stitching the three-dimensional or small-curved leather bags, shoes,etc.. Due to special unison feed, no wrinkle in light material and fine stitch in heavy material.

- Equipped with easy-operating safety clutch which would protect rotating hook from damage.
- With special designed postbed, suitable for stitching the small-curved portions & three-dimensional articles, such as the bottoms & gores & corners of the bags, baby's & children's shoes, boots, suitcases,etc..

