



富怡全自动单头缝纫机 (薄料)

Richpeace Single Head Automatic Sewing Machine (Thin Material)

Richpeace®

RPS-AT-01-900X600-AH



性能优势

Feature & Advantages

- 工作幅面大,最大工作面积1200X800mm
- 工作速度高,花样精准
- 花型任意设计,不受限
- 针迹均匀美观,底面线一致
- 自动剪线功能
- 标准中薄料缝制式,线迹稳定
- Large working area, maximum working area 1200X800mm
- Higher working speed with high precision
- Free to design any pattern, no limitation in making
- Best and even surface and bottom sewing stitch quality
- Automatic thread trimmer.
- Suitable for thin/middle thickness materials' sewing, stable stitch quality


适用范围

Application


服装部件 (领子、袋盖、袖子等)、先缝线再充绒羽绒服缝制,轻薄羽绒服、棉服缝制,遮阳帽沿、枕芯、枕套等双层或多层布料缝制
Garment parts (collar, flap, cuff, etc.), down jacket (sewing-filling), light down jacket, winter clothes, sunhat brim, pillow inner, pillow case, and all kinds of double or multi-layer cloth sewing.



Get this page



开放式气动夹料,夹持模板
稳定可靠
Open pneumatic clamping
system, hold template
tight and reliable



花型任意设计,富怡自主
研发模板CAD软件
No limitation for designing, with
Richpeace AutoSew CAD
software.



5.7寸操作箱,方便直观
5.7" inch computer control
panel, easy to operate



富怡独有专利钻绒解决方
案,解决先充绒自动缝制
的钻绒问题
Richpeace exclusive
downproofness technology to
avoid the down unthreading
the clothes.

产品型号 Model	RPS-AT-01-900X600-AH	RPS-AT-01-1200X800-AH
头数 Head Number	01	01
工作面积 (X x Y) Sewing Area (X x Y)	900X600mm	1200X800mm
缝线类型 Stitch Type	单针锁式线迹 Single needle lock stitch	
最高速度 Max. Sewing Speed	2,500 针/分钟 2,500 stitch/min	
针迹步长 Stitch Length	0.5-12.7mm	
最高存储针数 Max. Stitch Storage	2,000,000	
夹料方式 Clamp Drive	气动夹料 Pneumatic Clamping System	
压脚抬升高度 Presser Foot Lift Height	9mm (薄料机 Thin Material) 18mm (厚料机 Thick Material) 50mm/150mm (升降机头 High Lift Model)	
剪线装置 Thread Trimmer System	有 YES	
花样读取方式 Data Transfer	U盘 USB DISK	
旋梭 Rotary Hook	标准旋梭、二倍旋梭、三倍旋梭 Standard Rotary Hook, Jumbo Size Rotary Hook, Triple Size Rotary Hook	
电机 Motor	AC伺服电机 AC Servo Motor	
电源 Power Supply	单相220V, 三相220V, 380V Single Phase 220V, Three Phase 220V, 380V	
气压 Compressor Air	0.5Mpa, 1.7升/分钟 0.5Mpa, 1.7L/min	